

POS-615

POS System

Essae[®]
...for Excellence



Powered by the latest Core i3 & i5 Processor. Delivers exceptional Performance & Power even in the most demanding applications.



Technical Specifications

Model	POS-615C	
CPU	Intel Core i3 1115G4 11 th gen 3.00 GHz up to 4.10 Ghz Processor 6 MB Cache Memory	Intel Core i5 1235U 12 th gen 3.30 GHz up to 4.40 GHz Processor 12 MB Cache Memory
Operator Display		
Size	38.1 cm (15") TFT LCD with LED Backlight, Anti-glare	
Maximum Resolution	1024 x 768	
Brightness	350 nits	
Touch Screen	Projected Capacitive Touch (PCAP) - True Flat	
Memory		
Storage Memory	128 GB M.2 NVMe SSD or 256 GB NVMe SSD	
System Memory	4 GB DDR4 RAM 1 x SO-DIMM Slot (Expandable up to 32 GB)	
External Interface Ports		
USB	6	
Serial (DB9)	3 x COM	
Network	1 x Gigabit LAN	
Display Port	1 x HDMI	
Audio	1 x Line-out & Mic in	
Environmental		
Operating Temperature	5 °C ~ 40 °C	
Storage Temperature	-20 °C ~ 55 °C	
Power Adapter	DC 12 V / 5 A 60 W	
Dimension (W x D x H)	4° tilt angle : 382 mm x 220 mm x 356 mm 84° tilt angle : 382 mm x 294 mm x 300 mm	
Optional Accessories		
Printer	PR-65 and PR-75 Thermal printer, 79.5±0.5 mm and 82.5 ± 0.5mm paper, 220 mm/sec, Auto-cutter, 2D Barcode : QR code support, Interface : Serial+USB+LAN	
Cash Drawer	5-Bill/8-Coin Metal Cash Drawer with Lock & Key and Micro Switch	
MSR	3 Track-OPOS Compliant, USB interface	
Customer display	20 chars x 2 lines Customer Display 9.7 inch Second Display Non Touch	
Mounting Options	VESA-compliant Wall Mount Kit	
Net Weight	6.1 kg (approx)	
Operating System		
Operating System Supports	Windows 10 IoT Linux (subject to confirmation)	

Accessories



MSR



20 chars x 2 lines
Customer Display



9.7 inch Second display
Non-Touch