

POS-815

POS System

Essae[®]
...for Excellence



A wide choice of Sleek & Elegant POS System to power your Business



Technical Specification

Model	POS-815A	POS-815B	POS-815C
CPU	Rk3288, Quad-Core A17, 1.80 GHz	Intel Baytrail J1900 QUAD CORE 2.00 GHz Embedded, 2 MB Cache memory	Intel Core i3-6100U 2.30 GHz 3 MB Cache memory
Operator Display			
Size	38.1 cm (15") TFT LCD with LED Backlight, Anti-glare		
Resolution / Brightness	1024 x 768 / 350 nits		
Touch Screen	Projected Capacitive Touch (PCAP) – True FLAT		
Memory			
Storage Memory	16 GB eMMC Flash	128 GB Solid State Disk (SSD) or 500 GB HDD	
System Memory	2 GB DDR3 RAM	4 GB DDR3L RAM (expandable upto 8 GB)	4 GB DDR4 RAM (expandable upto 16 GB)
External Interface ports			
USB	4	6	4
Serial (DB9)	2	2	3
Network	1 x Gigabit LAN	1 x Gigabit LAN	2 x Gigabit LAN
Display Port	-	1 x VGA	1 x HDMI
Standard features	Wi-Fi & Bluetooth	-	
Factory options	-	Wi-Fi LAN module (Mini-PCIe)	
Audio	1 x Line-In, 1 x Line-out		
Environmental			
Operating Temperature	5 ⁰ C ~40 ⁰ C		
Power Adapter	DC 12 V/5 A 60 W		
Dimension (W x D x H)	382 mm x 256 mm x 355 mm		
Printer	Thermal printer, 79.5+- 0.5 mm paper, 220 mm/sec, Auto-cutter 2D Barcode : QR code support, Interface : Serial+USB+LAN		
Cash Drawer	5-Bill/8-Coin Metal Cash Drawer with Lock & Key and micro-switch		
MSR	3 Track-OPOS Compliant, USB interface		
Customer display	20 charsx2 linesCustomerDisplay 9.7 inch Second Display Non Touch		
Mounting Options	VESA-compliant Wall Mount Kit		
Net Weight	5.3 kg (approx)		
Operating System			
Operating System supported	Android 7.1.2 Nougat	Windows 10 IOT Enterprise 2016 LTSB Entry (64 bit) Windows Embedded POSReady 7 Linux (subject to confirmation)	Windows 10 IOT Enterprise 2016 LTSB Value (64 bit) Windows Embedded POSReady 7 Linux (subject to confirmation)

Accessories



MSR



20 chars x 2 lines Customer Display



9.7 inch Second display Non-Touch

Your representative