

# LS-600 Handheld Barcode Scanner



- ▶ Robust Design
- ▶ Easy to Configure
- ▶ IP54 Protection
- ▶ Good Scan Distance on Big Barcodes
- ▶ 32 Bit CPU, Strong Decode Ability on Difficult Barcodes

PERFORMANCE PARAMETER	
Light Source	Visible Laser Diode 650nm
Scan Pattern	Single Scan
Scan Rate	100 times/second
Scan Precision	4mil 200mm
Scan Width	20-350mm
Scan Depth of field	EAN-8, EAN-13, UPC-A, UPC-E, Code
Decode Capability	39, Code 128, EAN 128, Codabar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5,
Tilt	MSI,GS1,etc.
Elevation Angle	30
Deflection Angle	65
Support Interface	60
Print Contrast	USB
Mention Pattern	30% UPC/EAN 100%

Buzzer, Indicator  
Manual & Continue Scanning

MECHANICAL PARAMETER	
Size	L x W x H: 175mm x 73mm x 102mm
Weight	238g
Material	ABS + PC
Cable	Standard 2M straight

ELECTRICAL PARAMETER	
Voltage	5VDC
Operating Current	90mA
Static Current	40mA

ENVIRONMENTAL PARAMETER	
Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C
Humidity	5% to 85% Relative Humidity, Non-Condensing
Light Levels	Daylight, 5000Lux
Drop Resistance	Designed to Withstand 1.5M Drops

\*Specifications are Subject to Change